



NUM'AXES

SKU	Designation	French Law	Length (cm)	Width (cm)	Height (cm)	Weight (g)	MSRP
NUM535	Piège photographique PIE1051	Vente libre	9.6	7.6	12.8	292	328.00 € incl. tax

The PIE1051 camera trap is the most compact device in the Num'axes range with image sending by MMS or e-mail.

SIM card provided: 4 photo transmission packages available

- Remote control by mobile app
- 4G = faster transmission and energy saving
- Invisible LEDs, range up to 20m
- Photo resolution up to 24 MP / 1 to 5 photos per trigger
- Wide-angle lens: 100° field of view
- Trigger speed: 0.5 seconds
- 2.4" color screen
- 8 AA batteries (alkaline or rechargeable Ni-MH) Compatible with external power supply
- Delivered without batteries or SD card. SIM card provided.

With the PIE1051 camera trap, you will be notified as soon as a photo or video is taken by sending an MMS or an email.

As soon as the SIM card is inserted, the device automatically detects the mobile operator and provides the corresponding sending parameters (works in 2G, 3G and 4G).

The PIE1051 camera trap can be set and triggered remotely through a free mobile application available on Android and ios.

Wide detection angle (80 °) and wide shooting angle (100 °)!

Features of the PIE1051 camera trap

- Angle of view: **100 °**
- PIR sensor (motion detector):

- Detection angle: **100 °**
- Detection distance: about 20m
- Adjustable sensitivity: low / medium / high
- Infrared flash:
 - Invisible black LEDs
 - Range: about 20 m
 - Possibility of inhibiting some of the LEDs:
 - avoids overexposed night photos / videos
 - useful if you want to place the camera close to the subject to be photographed / filmed
 - Infrared flash with automatic activation according to the brightness
- **Possibility to configure and trigger the device remotely using a free mobile application (Android / iOS) - Application name: PIE1051**
- Sends photos by MMS or email (works in **2G** , **3G** and **4G**)
- Recipients of photos and / or videos:
 - You can enter 1, 2, 3 or 4 mobile phone numbers (recipients will only receive MMS and therefore only photos, no videos)
 - You can enter 1, 2, 3 or 4 e-mail addresses (recipients will receive MMS or e-mails depending on the settings chosen and therefore photos and / or videos)
- When inserting the SIM card (standard size), **the device automatically detects the mobile operator and informs the corresponding MMS / email sending parameters** (only if the operator is part of the list of operators preprogrammed in the 'apparatus').
- Capture modes:
 - Photo: from 1 to 5 photos per trigger
 - Video with audio recording: programmable duration from 5 to 59 seconds
 - Photo + Video with audio: a photo then a video is taken at each trigger
- Photo resolution: 5 MP / 8 MP / 12 MP / 24 MP
- Video resolution: VGA / HD 720P / Full HD 1080P
- Night mode:
 - Adjustable: maximum range / balanced / minimum blur
 - A longer or shorter exposure increases or decreases the range of the infrared flash
- **PIR detection mode** : the device takes photos or videos when the PIR (motion detector) sensor detects activity in the area it covers
- **Time Lapse mode** : photos or videos are taken automatically at regular time intervals during a user-defined time slot
- Marking on photos and videos: time, date, temperature, moon phase, device serial number, battery charge level
- Memory: SD or micro SD card with adapter from 4 GB to 32 GB, class 10 minimum (not supplied). The device also works with the micro SD card with 64 GB adapter from NUM'AXES. 64 GB memory cards from other brands may not work. You can get micro SD cards with adapter at any time on this site (8 GB, 16 GB, 32 GB or 64 GB).
- **Loop recording on memory card** :
 - User programmable: ON / OFF
 - When the memory card is full, the camera records new photos / videos by deleting the oldest photos / videos.

Reliable and efficient

- 2 years warranty
- Designed to withstand bad weather (IP66)
- Trigger speed: 0.4 seconds

Ergonomics of the PIE1051 camera trap

- Weight: 661 g (with batteries)

- Dimensions: 148 x 117 x 78 mm
- Power supply: 8 AA alkaline batteries or 8 AA Ni-MH rechargeable batteries (not included) - **These batteries can be purchased at any time on this website.**
- Optional external power supply possible: power supply unit, solar panel
- 2 inch (~ 5 cm) TFT color LCD display
- USB 2.0 port for downloading files

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.