

EAW tilting assembly with Ø30 mm rings and Base Height 18 mm

https://www.simac.fr/en/produit-3832-EAW-tilting-assembly-with-30-mm-rings-and-Base-Height-18-mm













Plus de visuels disponibles sur le site



SKU	Designation	French Law	Diam. (mm)	Mounting	MSRP
MEL301800	Ø30 mm BH18 mm weaver	Vente libre	30	11mm rail	175.00 € incl. tax
MEL301801	Ø30 mm BH18 mm weaver rear elbows	Vente libre	30	11mm rail	270.00 € incl. tax
MEL301802	Ø30 mm BH18 mm weaver inside elbows	Vente libre	30	11mm rail	270.00 € incl. tax

Tilting assembly in two pieces of aluminum with rings with a diameter of 30 mm and a base with a height of 10 mm. The attachment to the rifle case is made by means of a lever.

3 versions available: without elbows, with rear elbows and with interior elbows.

There are several ways to mount a rifle scope, but the most common is the option with rings. It has many advantages, including its affordable price and the fact that it is available in the largest number of versions. Many telescopes today require a 30mm mount because their main tube is 30mm in diameter. This means that to connect your scope to the firearm you need 30mm rings for mounting. The most important thing when mounting a rifle scope with rings is to know the proper force needed to secure the rings. If you exceed this limit, the structural integrity of the scope will be compromised. Rings can also leave a visible mark if not tightened properly. The tightening torque must not exceed 2.2 Nm.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.