



Plus de visuels
disponibles
sur le site

SKU	Designation	French Law	Twilight fact Min	Twilight fact Max	Field max 100 m	Field min 100 m	Length (cm)	Width (cm)	MSRP
OI2220	Infiray Tube TH50 V2	Vente libre	13.23	26.46	15.4	12.3	36.5	7.5	4899.00 € incl. tax 1959.60 € incl. tax

The new TH50V2 is designed to deliver unprecedented comfort, exceptional clarity and absolute precision.

The TH50V2 builds on the success of the TH50 with the addition of the optional LRF function and the built-in mic function, while retaining the excellent features such as the 640x512 12um sensor, 50mm optics and 2560x2560 AMOLED display 1.03".

- **Ultra-precision enhanced by optional (enhanced) LRF:** The TH35V2/TH50V2 is able to provide distance measurement on the screen when the LRF is connected to the device via Bluetooth, giving you more chances of hitting with each shot.
- **Built-in Microphone (Upgraded):** The TH35V2/TH50V2 is equipped with a MIC function, which allows customers to record voice when recording.
- **Traditional Design:** Traditional style housing allows for mounting with standard 30mm rings like a typical day scope.
- **12um 640*512 High Capacity Sensor:** The TH35V2/TH50V2 is the high-end thermal scope of the Tube series. It is equipped with the market-leading InfiRay 12um 640x512 sensor and an advanced image processing algorithm.
- **1.03 inch AMOLED screen with 2560x2560 resolution:** TH35V2/TH50V2 adopts particular 2560x2560 1.03" AMOLED screen to provide optimal viewing experience with excellent optical parameters. There is no need to fix the screen as you did before, avoiding visual fatigue caused by long viewing time.
- **Ultra-clear mode:** With Ultra-clear mode, the TH50V2 can still provide a clear and delicate image even in adverse weather conditions such as thick fog or rain.
- **More Accurate Zeroing:** TH50V2/TH35V2 is capable of reaching 1.2cm/1.71cm per unit at 100m when zeroing. Each scale unit is smaller. Therefore, zeroing can be more accurate.
- **Smooth Magnification:** The TH35V2/TH50V2 is able to magnify the image smoothly without flickering or stuttering, which brings viewing comfort to users.

- **2600m Detection Range:** Thanks to the combination of an extraordinary sensor and powerful 50mm optics, the TH50V2 can achieve a detection range of 2600m.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.