



**NOUVEAU**

SKU	Designation	French Law	Twilight fact Min	Twilight fact Max	Field max 100 m	Field min 100 m	Length (cm)	Weight (g)	MSRP
LDTF71	Falke 1-8x26 FFP SAS MRAD	Vente libre	5.09	14.42	3.96	32	25	680	740.00 € incl. tax

**Optimize your shooting performance with the FALKE Pro Series 1-8x26 MRAD scope, combining speed and precision thanks to its illuminated SAS reticle.**

The FALKE Pro Series 1-8x26 MRAD scope is designed for shooters looking for versatility and efficiency. Its SAS (Speed Aiming Solution) reticle in the first focal plane (FFP), illuminated on 8 levels, ensures rapid target acquisition. With a robust 34 mm body and a weight of 680 g, it offers exceptional durability. The precise adjustments of 0.1 MRAD per click guarantee optimum precision during your shooting sessions.

- **Magnification:** 1x to 8x
- **Lens diameter:** 26 mm
- **Tube diameter:** 34 mm
- **Length:** 25 cm
- **Weight:** 680 g
- **Parallax Setting:** Fixed at 100m
- **Adjustment range (windage and elevation):** 35 MRAD
- **Reticle:** SAS in first focal plane, illuminated in red with 8 brightness levels
- **Correction per click:** 0.1 MRAD (1 cm at 100 m)

The **FALKE Pro Series 1-8x26 MRAD riflescope** is a high-performance optic, ideal for dynamic shooters and close-quarters combat (CQB) situations. Its design integrates the advantages of a traditional riflescope and a reflex sight, thus offering remarkable versatility.

### **SAS (Speed Aiming Solution) reticle:**

Developed by FALKE, the SAS reticle is positioned at the first focal plane (FFP), enabling rapid target acquisition. At low magnifications, the reticle's outer circle facilitates intuitive targeting, while at higher magnifications, this circle fades to reveal range-finding marks and additional cues for long-range shots. The reticle is illuminated in red with 8 brightness levels, ensuring optimum visibility in a variety of light

conditions.

**Robust construction:**

The scope body is made of aircraft-grade aluminum with a diameter of 34 mm, providing increased strength while maintaining a reasonable weight of 680 grams. This construction ensures resistance to the most demanding conditions encountered in the field.

**Accuracy of adjustments:**

The adjustment turrets provide precise clicks of 0.1 MRAD, equivalent to a 1 cm adjustment at 100 meters. The windage and elevation adjustment ranges are 35 MRAD, allowing fine adjustments for precise shots at various distances. The turrets are protected by sturdy screw-on caps, preventing accidental adjustment.

**Accessories included:**

The scope comes with several accessories to enhance the user experience:

- Dust caps to protect lenses.
- Sun visor to reduce unwanted glare.
- Screw-on magnification adjustment lever for quick adjustments.
- Kill-flash system to minimize front lens flare.

These accessories ensure optimal protection of the optics and increased adaptability to different shooting conditions.

*Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.*