

Le Choix des Armes https://simac.fr//en/produit-4459-PARD-Leopard-LE6-50-LRF-Thermal-Monocular-Scope













NOUVEAU

SKU	Designation	French Law	Weight (g)	MSRP
OR1316501	Pard TH monoculaire LEOPARD diam.50 / 640*512 / LRF	Vente libre	360	2315.00 € incl. tax

640×512 thermal imaging with 1000m laser rangefinder and long range up to 2600m.

High-performance thermal monocular equipped with a 640×512 pixel VOx sensor, 50 mm objective lens and integrated laser rangefinder, optimized for long-distance observation even in total darkness.

- **■** Thermal sensor:
- Sensitivity:
- **■** Objective:
- Digital zoom:
- Detection:
- Laser rangefinder:
- Screen:
- **■** Connectivity:
- **■** Recording:
- **■** Battery life:
- Protection index:
- **■** Weight:

Long-range thermal power for professional or security outings

Perfect for nighttime surveillance, long-range scouting, or tracking game in open areas, this monocular combines optical performance with field agility. Its 50mm objective lens provides a detection range of up to 2,600m while maintaining a compact, easy-to-handle design.

- Ultra-high resolution: 640 × 512 VOx sensor with NETD ? 20 mK for remarkably sharp images even in adverse conditions
- Integrated rangefinder: laser rangefinder up to 1000 m with an accuracy of approximately ± 1 m, essential for ballistic assisted shooting

- Multiple visual modes: image palettes (WhiteHot, BlackHot, Edge, RedHot, IronHot, Sky) and scene modes (City, Rain, Forest) to adapt to any environment
- **PIP and thermal tracking:** picture-in-picture and hot track function to identify and maintain the target even when moving
- **Video/Photo on SD card:** Recording function with resolution up to 2048×1536 in photo or 1024×768 in video, micro SD support up to 128 GB
- **Field ergonomics:** intuitive interface even with gloves, diopter dial from –5 to +5 D, light weight of ~360 g for comfortable prolonged observation
- **Professional standards:** up to 6 hours of battery life on 18650 battery, USB-C charging, HDMI output for external streaming, Wi-Fi for connecting to the PardVision2 app
- Certified robustness: aluminum and composite housing, IP67 certified and usable between -30 °C and +55 °C, resistant to extreme conditions

This Leopard LE6?50 LRF monocular combines extreme range, image quality and field reliability, perfectly suited to BtoB professionals looking for a powerful, compact and immediately operational thermal tool.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.