



INNOMOUNT

NOUVEAU

SKU	Designation	French Law	Length (cm)	Height (cm)	Weight (g)	Mounting	MSRP
IM44TD70-90000	Innomount monobloc / picatinny / TD70 / BH33mm	Vente libre	2	3.3	150	21mm rail	540.00 € incl. tax

The ZERO mounting with torque locking for constant accuracy.

The **INNOMOUNT ZERO** mount is specifically designed for the **InfiRay TD70L** on **Weaver/Picatinny** rails. Its exclusive **Torque Lock** system guarantees consistent clamping force, ultra-fast tool-free removal, and excellent impact point repeatability. Its high-strength aluminum and hardened steel construction ensures robustness, precision, and durability.

- **Compatibility:** InfiRay TD70L
- **Compatible rail:** Weaver / Picatinny
- **Mounting type:** INNOMOUNT ZERO with Torque Lock
- **Necklace diameter:** 30 mm
- **Collar width:** 15 mm
- **Collar spacing:** 67 mm
- **Center-to-center distance of clamping axes:** 60 to 115 mm
- **Construction height:** 33 mm
- **Total length:** 200 mm
- **Weight:** 150 to 180 g depending on the version
- **Materials:** High-strength aluminum and hardened steel

ZERO technology: intelligent tightening

The **INNOMOUNT ZERO** mount incorporates the exclusive **Torque Lock** system, designed to automatically apply a constant clamping force. Unlike a conventional locking system, it compensates for slight variations in tolerances between different **Weaver** or **Picatinny** rails. The result is a consistent and perfectly repeatable attachment, without complex adjustments.

Quick disassembly accessible to all

Two simple steps are all it takes to install or remove the lens, without any tools. Even a user unfamiliar with this type of mount quickly gets the hang of it. In practice, this simplicity becomes a real advantage when you want to change lenses or transport your equipment separately.

Designed for the InfiRay TD70L

This model is specifically designed for the **InfiRay TD70L thermal telescope** equipped with a **30mm tube** . The 15mm wide rings ensure a secure hold on the optics while effectively distributing mechanical stress. The 67mm spacing guarantees a perfect fit for this platform.

A robust and durable construction

The body is machined from **high-strength aluminum** to offer an excellent rigidity-to-weight ratio. The mechanical components are made of **hardened steel** , guaranteeing excellent wear resistance and high reliability through repeated use. It's the kind of assembly you quickly forget about... because it simply does its job.

A profile designed to preserve balance

With a **build height of 33 mm** and a total length of **200 mm** , this mount offers stable optic positioning while maintaining excellent balance between the weapon and optics. Its streamlined design integrates seamlessly into modern setups.

FAQ

What is the Torque Lock system?

The Torque Lock system automatically applies a constant clamping force and compensates for slight differences in tolerances between Weaver and Picatinny rails, ensuring a consistently even fit.

Does the assembly require any tools?

No. Assembly and disassembly are carried out entirely by hand thanks to the INNOMOUNT ZERO system.

Is this setup exclusively compatible with the InfiRay TD70L?

Yes. This version is specifically developed for the InfiRay TD70L to guarantee a perfect fit and optimal repeatability.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.