



NOUVEAU

SKU	Designation	French Law	Length (cm)	Height (cm)	Weight (g)	Colors	Mounting	MSRP
IMP1400	Picatinny rail/Tikka T3	Vente libre	15.8	0.8	135	Black	21mm rail	150.00 € incl. tax
IMP1400M	picatinny rail/ Tikka T3 20 MOA	Vente libre	15.8	0.8	135	Black	21mm rail	150.00 € incl. tax

Two Innomount Picatinny rail configurations to equip your Tikka T3 or T3x.

Innomount one-piece Picatinny rails for the Tikka T3 and T3x are available in **standard** or **20 MOA pre-tilt** versions. Made from **blued steel**, they guarantee maximum rigidity, excellent mounting repeatability, and universal compatibility with Picatinny optics.

- **Brand:** Innomount
- **Compatibility:** Tikka T3 and Tikka T3x
- **Available versions:** Standard or pre-tilted 20 MOA
- **Type:** One-piece Picatinny rail
- **Standard:** Picatinny MIL-STD-1913
- **Material:** Bronzed steel
- **Height:** 8 mm
- **Length:** 158 mm
- **Dimension A:** 21.9 mm
- **Dimension B:** 82.2 mm
- **Dimension C:** 21.9 mm
- **Weight:** Approximately 135 g
- **Supplied with:** 4 fixing screws N00001

Two mounting options depending on your practice

This range of **Innomount Picatinny rails** allows you to equip the **Tikka T3** and **T3x** rifles with a perfectly adapted base. Two versions are available to suit different uses: a **standard** model for classic mounting and a **pre-angled version with a 20 MOA angle**, particularly appreciated for medium and long-range shooting.

Why choose a rail with a 20 MOA pre-tilt?

The **20 MOA** version tilts the optics slightly forward to maintain a greater range of elevation adjustment. This configuration allows you to fully utilize the capabilities of scopes designed for long-range shooting, while preserving a perfectly rigid mount. For everyday use or more typical distances, the standard version remains perfectly adequate.

One-piece steel construction

Made from **blued steel**, these rails offer excellent mechanical resistance and superior rigidity. This feeling of solidity is immediately noticeable and inspires confidence, especially during disassembly or after numerous shooting sessions. The finish effectively protects the rail while maintaining a discreet aesthetic perfectly suited to the rifle.

Universal Picatinny compatibility

The profile conforms to the **Picatinny MIL-STD-1913 standard**, ensuring compatibility with the majority of rings, scopes, red dot sights, and other accessories available on the market. Precision-machined grooves ensure a secure lock and excellent mounting repeatability.

Optimized positioning of your optics

Thanks to their **158 mm** length, these rails allow for easy optic positioning according to the desired eye relief or the shooter's physique. This adjustability improves user comfort while promoting a natural and consistent shooting position.

FAQ

What is the difference between the standard version and the 20 MOA version?

The standard version is suitable for most uses. The version with 20 MOA pre-tilt allows for a greater range of elevation adjustment for medium and long-range shooting.

Are these rails compatible with the Tikka T3 and T3x?

Yes. Both versions are specifically designed for the Tikka T3 and T3x rifles and ensure a perfectly fitting mount.

Are the mounting screws included?

Yes. Each rail comes with four N00001 fixing screws for immediate installation.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.