Piexon JPX2 Gen 2 Jet Protector

https://simac.fr/en/produit-4849-Piexon-JPX2-Gen-2-Jet-Protector









Plus de visuels disponibles sur le site

NOUVEAU

SKU	Designation	French Law	Length (cm)	Weight (g)	MSRP
JPX102	without laser	Vente libre	19.5	368	359.00 € incl. tax
JPX102L	with laser	Vente libre	19.5	382	449.00 € incl. tax

A compact format, two Piexol charges and a fast-action trigger.

The **Piexon JPX2 Gen 2** combines a compact design with a **Speedloader** magazine holding two **Piexol 400kS** active ingredient charges. Its double-action trigger system with automatic switching allows for quick and intuitive handling. The slightly enlarged grip improves handling while maintaining the model's compact size.

- **Versions:** without laser or with integrated laser
- **Loader:** Speedloader with two active substance charges
- **Active substance:** Piexol 400kS
- **Advertised range:** 1.5 to 7 m

- **Versions:** without laser or with integrated laser
- **Dimensions (L x W x H):** 195 x 37 x 111 mm
- **Weight of standard receiver:** 368 g
- **Weight of receiver with laser:** 382 g
- **Weight of the charged charger:** 120 g
- **Loader:** Speedloader with two active substance charges
- **Active substance:** Piexol 400kS
- **Advertised range:** 1.5 to 7 m
- **Safety distance:** 1.5 m
- **Jet speed at 1.5 m:** 80 m/s, or 290 km/h
- **Trigger system:** double action only, automatic switching
- **Release resistance:** 8.5 kg
- **Temperature range:** -20 °C to +60 °C

In France, the JPX2 Gen 2 is a category D device. It can be purchased freely by an adult. Wearing and transporting it outside the home are prohibited without a legitimate reason.

Two configurations available

The **JPX2 Gen 2** is available in a standard version or with **an integrated laser** . The version without a laser retains the 368g receiver, while the laser configuration weighs 382g. This distinction allows users to choose the equipment based on their aiming preferences and desired level of compactness.

Dual-charge Speedloader

The removable magazine holds two **Piexol 400kS** charges. Its quick replacement facilitates reconfiguration after use, while maintaining a simple and compact design. The loaded magazine weighs 120 g.

Ergonomics and materials

The slightly enlarged handle improves hand contact without sacrificing the compact size of the previous model. The **steel-polymer composite** receiver combines rigidity and strength, with a construction designed to maintain handling quality over time.

Propulsion and conditions of use

The Jet Protector's proprietary propulsion system is designed to operate without requiring prior pressurization. The manufacturer claims resistance to headwinds and rain, as well as a temperature range of -20°C to +60°C. The jet reaches a speed of 80 m/s at 1.5 m, with a claimed range of 1.5 to 7 m.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.